


NIKOMAX 19", 1U, 24 ports, 1000BASE-T, 2.5GBASE-T, ATM-25, ATM-51, ATM-155, 100VG-AnyLan, TR-4, TR-16 Active, TR-16 Passive, RJ45/8P8C, 110/KRONE, T568A/B, UTP Cat5e

(- - -)

NIKOMAX NMC-RP48UE2-AN-2U-BK
19"
«AN»



1 .
2 .
48 .
8 .
1 .

10BASE-T, 100BASE-TX, 100BASE-T4, 1000BASE-T, 2.5GBASE-T, ATM-25, ATM-51, ATM-155, 100VG-AnyLan, TR-4, TR-16 Active, TR-16 Passive

ISO/IEC11801, EN 50173 TIA/EIA-568

	5e
	100
	48
	2U
	RJ45/8P8C
	-24-22 AWG (0,50-0,65)
IDC ()	110/KRONE
	T568A/B
	750-
	19"


	1,5
	(50) (100)
IDC	
IDC	(100)
	,
	,
	UL94V-0

	1 - 100
	1000 , 60 1
	20
IDC	2,5
(NVP)	2,5
(500)	500 M *

	30
	80
	-40 +70 °C
	0 +50 °C
	-10 +60 °C

	5
	25

	500 105 80
	1,710
	0,004200 ³



« »

40 +70°C.

1.
2.

3.

4.
5. ()