

Memory Module Specifications

KSM48R40BS4TMI-32MDI

32GB 1Rx4 4G x 80-Bit

PC5-4800 CL40 Registered EC8 288-Pin DIMM

DESCRIPTION

Kingston's KSM48R40BS4TMI-32MDI is a 4G x 80-bit (32GB) DDR5-4800 CL40 SDRAM (Synchronous DRAM), 1Rx4, ECC, memory module, based on twenty 4G x 4-bit FBGA components. The SPD is programmed to JEDEC standard latency DDR5-4800 timing of 40-39-39 at 1.1V. Each 288-pin DIMM uses gold contact fingers. The electrical and mechanical specifications are as follows:

FEATURES

- Power Supply: VDD = 1.1V Typical
- VDDQ = 1.1V Typical
- VPP = 1.8V Typical
- VDDSPD = 1.8V to 2.0V
- On-Die ECC
- x80 ECC (x40, 2 independent I/O sub channels)
- 32 internal banks
- Hard/Soft Post Package Repair
- Sideband access with I3C/I2C
- PCB: Height 1.23" (31.25mm)
- RoHS Compliant and Halogen-Free

SPECIFICATIONS




| | |
|--|-------------------|
| CL(IDD) | 40 cycles |
| Row Cycle Time (tRCmin) | 48ns(min.) |
| Refresh to Active/Refresh Command Time (tRFCmin) | 295ns(min.) |
| Row Active Time (tRASmin) | 32ns(min.) |
| Row Precharge Time (tRPmin) | 16ns(min.) |
| UL Rating | 94 V - 0 |
| Operating Temperature | 0° C to +95° C |
| Storage Temperature | -55° C to +100° C |

Module Assembly

DRAM: Micron (D-Die)
RCD: IDT/Renesas
PMIC: TI
SPD Hub: Montage
TS: IDT/Renesas

Continued >>

MODULE DIMENSIONS



The product images shown are for illustration purposes only and may not be an exact representation of the product.
Kingston reserves the right to change any information at anytime without notice.