



USB C <--> HDMI+RJ45+USB +PD adapter cable allows a device with USB connector, as connected HDMI units.

The scope of application of this cable is personal computers, workstations, server equipment, telecommunication networks, SCS networks.

This unit is used to connect the computer to a GSM modem or stationary modem to access the network.

Technical Specifications

Physical Properties	
Model	TAU704
Outputs	1. USB-C 1 PD3.0 60/87/100W 2. USB-C 2 Data-C 2X , Support 5Gbps 3. USB-A USB3.0 Support 5Gbps, 1 ports for data syncing. 4. HDMI Up to 4K@60Hz 5. RJ45 Up to 1000M 6.SD/TF Support 2 cards reading simultaneously (USB2.0)
Cable type	PVC jacket
Cable Shield Material	Aluminum-Mylar Foil with Braid
Conductor Gauge	30AWG
Conductor Material	Oxygen Free Copper
Shell Material	Aluminium alloy case + PVC molding
Color	Grey
OS Support	Works with Windows/Linux/Mac OS/Android
Environmental	
Operating Temperature	-10°C to 50°C
Storage Temperature	-10°C to 50°C
Humidity	0%RH ~ 85%RH

Features

- Plug and play, no drivers required.
- HDMI port Supports 3840x2160 @ 60Hz. backwards compatibility with HD 1080p and 720p.
- Support USB3.0, also backward compatible with USB2.0/USB1.1.
- Compatible Devices Various models of MacBooks, Mac Pro, iMac, Surface, XPS, laptops, desktops, smartphones, and tablets with a Type C port.
- System environment compatible with Windows/Linux/Mac OS/Android.
- Please make sure that your laptop Type C port support DisplayPort Alt Mode(video output).

Model List

TAU704	USB HUB TYPE C to USB 3.0+USB C 3.0+SD+TF+RJ45+HDMI+USB-C PD
--------	--