



Technical Specifications

Physical Properties	
Model	TUD5521
Cable Length	1m,1.8m
Interface	Input: 1x USB Type-A Male
	Output: 1x DC5.5*2.1 Male
Connector Plating	Nickel-plated
Cable type	PVC jacket
Conductor Gauge	22AWG
Conductor Material	Oxygen Free Copper
Cable Outer Dimension	3.5mm ± 0.2mm
Outer model	PVC injection molding
Color	Black
Performance	
Power	Max. support 2A
OS Support	Works with Windows, MAC OS X, Chrome OS, Linux
Environmental	
Operating Temperature	-10°C to 50°C
Storage Temperature	-10°C to 50°C
Humidity	0%RH ~ 85%RH

Features

- Plug and play, no drive needed.
- Compatible with network device and Home electronic appliances, such as Camera, Webcam Route, Recorder, DVR, Hard Disk Box, Mini fan, LED Pixel Light and more DC5.5*2.1 devices.
- The cable perfect compatible with universal AC power adapters supplies. Max. support 2A, also support 1.5A,1A, 500mA 700mA 300mA etc.
- This DC cable is made of environmentally friendly PVC material and pure oxygen free copper, fast charging and not damage the equipment.
- Reinforced connector design, resistance to plugging, not afraid of bending, strong and durable.

Model List

TUD5521-1M	USB A-->DC5.5*2.1 (1M) , Telecom
TUD5521-1.8M	USB A-->DC5.5*2.1 (1.8M) , Telecom