

POWER EVOLVED



Introducing the MWE Bronze V3, the evolutionary next step in Cooler Master power and the ATX 3.1 upgrade to our MWE Bronze V2 PSU. With features such as 80 Plus Bronze efficiency, a DC-to-DC + LLC circuit design, and a quiet HDB fan cooling, the V3 provides valuable performance in multiple dimensions.

Several changes and additions improve the overall user experience. Together, these design choices deliver an advanced PSU that is highly efficient and reliable. With an embossed cable, exceptional temperature resilience and a 5-year warranty, the MWE Bronze V3 will evolve your machine.

MWE BRONZE 750 V3

Quiet HDB fan: A hydrodynamic bearing fan delivers long-lasting quiet and effective cooling.

80 Plus Bronze efficiency certification: This unit is certified to achieve more than 85% efficiency at typical loads in a 115V test.

High temperature resilience: A 40°C maximum operating temperature allows for pushing your machine to the limits with overclocking and other high-intensity applications.

Embossed cable: An embossed cable texture provides a softer and overall improved grip with a pleasing aesthetic.

ATX 3.1 support: Compliant with ATX 3.1 to fully support a peak power 1.5 times higher than the rated maximum wattage, this unit is ideal for use with the 40 series GPUs.

Single +12V rail: All power comes from a single +12V source, ensuring consistent output through all connected cables.

DC-to-DC technology: The DC-DC circuit design offers reliable, stable output to all connected components.

2 EPS Connectors: Two 4-pin EPS connectors are included for universal compatibility with current-gen motherboards.

5-year warranty: This unit comes with a standard limited manufacturing warranty of 5 years from the date of purchase.



FEATURE HIGHLIGHTS



Quiet HDB fan

A hydrodynamic bearing fan delivers long-lasting quiet and effective cooling.



High temperature resilience

A 40°C operating temperature allows for pushing your machine to the limits.



80 Plus Bronze efficiency certification

Certified to achieve more than 85% efficiency at typical loads in a 115V test.



Embossed cable

An embossed cable texture provides a softer and overall improved grip with a pleasing aesthetic.



5-year warranty

This unit comes with a standard limited manufacturing warranty of 5 years from the date of purchase.



ATX 3.1 support

After passing the ATX 3.1 peak power test, this unit is 40 series ready.

SPECIFICATIONS

Product Name	MWE Bronze 750 V3								
Item Code	MPE-7501-ACAAW-3B								
ATX Version	ATX 12V Ver. 3.1								
PFC	Active PFC								
Input Voltage	100 - 240V								
Input Current	10 - 6A								
Input Frequency	50 - 60Hz								
Dimensions (L x W x H)	140 x 150 x 86mm								
Fan Size	120 mm								
Fan Bearing	HDB								
Efficiency	≥ 85% @ Typical Load								
80 PLUS Rating	80 PLUS Bronze								
ErP 2014 Lot 3	Yes								
Operating Temperature	0 ~ 40°C								
Power Good Signal	100 - 150ms								
Hold Up Time	≥ 16ms								
MTBF	>100,000 hours @ 25°C ambient								
Protections	UVP / OVP / OPP / OTP / SCP								
Regulatory	cTUVus, TUV, CE, FCC, BSMI, CCC, EAC, RCM, UKCA, RoHS2.0 / BIS, KC (based on region's request.)								
Connectors	ATX 24 Pin	x1 = 1x (500mm)							
	EPS 8Pin / 4+4 Pin	x2 = 1x (550+120mm)							
	SATA	x6 = 2x (400+150+150mm)							
	Peripheral 4 Pin	x3 = 1x (400+150+150mm)							
	PCI-e 6+2 Pin	x4 = 2x (500+120mm)							
AC INPUT									
100-240V~ 10 - 6A 50 - 60Hz									
DC OUTPUT		+3.3V	+5V	+12V	-12V				
		20A	20A	62A	0.3A				
TOTAL POWER		120W	744W	3.6W	15W				
			750W						

PACKING INFORMATION

Cable Type	EAN	UPC
MPE-7501-ACAAW-3BUS	4719512145777	884102118098
MPE-7501-ACAAW-3BUK	4719512145784	884102118104
MPE-7501-ACAAW-3BEU	4719512145791	884102118111
MPE-7501-ACAAW-3BST	4719512145807	884102118128
MPE-7501-ACAAW-3BAU	4719512145814	884102118135
MPE-7501-ACAAW-3BBR	4719512145821	884102118142
MPE-7501-ACAAW-3BTW	4719512145845	884102118166
MPE-7501-ACAAW-3BJP	4719512145852	884102118173
MPE-7501-ACAAW-3BIN	4719512145869	884102118180
MPE-7501-ACAAW-3BTH	4719512145876	884102118197

Net Weight	1.75 kg / 3.8581 lb
Gross Weight	2.15 kg / 4.7421 lb
Package Dimensions	245 x 190 x 110mm (9.65 x 7.48 x 4.33")
Carton Dimensions	570 x 260 x 215mm (22.44 x 10.24 x 8.46")
Unit / Carton	5 pcs
Carton / Pallet	32 pcs

- All images and descriptions are solely for example purposes.
- Specifications, features, and prices are subject to change without notice.
- Specifications, appearances, and features may vary by model and region. Please refer to official specification pages for full details.
- Unless otherwise stated, all performance claims are based on theoretical performance. Actual figures may vary in real-world situations.
- Any configuration other than original product configuration is not performance guaranteed.