



Data cable.

The interface connection cable is designed to connect devices with an HDMI (M) connector (digital signal) to devices with an micro HDMI (M) connector (digital signal).

The scope of application of this cable is personal computers, workstations, server equipment, telecommunication networks, SCS networks.

Technical Specifications

Physical Properties	
Model	TCG286
Cable Length	1.0M, 2M,
Interface	Input HDMI 19PIN, Male
	Output micro HDMI 19PIN, Male
Cable type	PVC jacket
Cable Shield Material	Aluminum-Mylar Foil with Braid
Conductor Gauge	23AWG
Conductor Material	Oxygen Free Copper
Cable Outer Dimension	$7.3 \pm 0.2\text{mm}$
Outer model	PVC molding
Color	Black
Performance	
Maximum Digital Resolutions	8K@60, 4K@120
OS Support	Works with Windows, MAC OS X, Chrome OS
Environmental	
Operating Temperature	-10°C to 50°C
Storage Temperature	-10°C to 50°C
Humidity	0%RH ~ 85%RH

Features

- Supports up to Supports resolutions up to 8K@60HZ
- Double shields effectively protect against EMI interference and provide more stable signal transmission.
- High purity Oxygen free copper inside ensures 0.01% transmission loss.
- With 2x ferrite cores,protected against electromagnetic interference.
- Plug and play, no drivers required.

Model List

TCG286-1M	Cable HDMI-19M --- Micro HDMI-19M ver 2.1+3D/Ethernet
TCG286-2M	Cable HDMI-19M --- Micro HDMI-19M ver 2.1+3D/Ethernet



The HDMI Ethernet channel can be used to connect two or more HDMI-compatible devices with Internet connections of up to 100 Mbps.