



NWA90BE

BE5100 4-Stream WiFi 7 Dual-Radio NebulaFlex Access Point

The Zyxel NWA90BE is a WiFi 7 access point designed to provide an ideal feature set for small businesses, SoHo users, and small spaces seeking an affordable upgrade to WiFi 7. Built for home offices, compact workplaces, and homes, it offers an effortless path to WiFi 7 with faster speeds and reliable, wide-area coverage.

Powered by a Qualcomm quad-core CPU, the BE5100 (2.4GHz: 2x2:2, 5GHz: 2x2:2) dual-radio access point delivers ultra-fast WiFi 7 speeds of up to 5.1Gbps, ensuring enterprise-grade performance in a compact design. Its 2.5GbE uplink unlocks the full potential of WiFi 7 for high-speed connectivity.

With a straightforward setup via Nebula Cloud Networking, you can quickly configure the access point, set up separate networks for work and family use, and start enjoying ultra-fast WiFi 7 speeds.

Additionally, with support for a captive portal and IEEE 802.1X authentication, the NWA90BE not only offers small business users enterprise-level security to protect their networks but also provides flexible options to customize wireless network login pages for marketing and brand recognition.

Zyxel's NWA90BE uses Smart Mesh MLO technology to create dynamic wireless links—no more messy cables or complex setups. Unlike traditional mesh systems limited by single-radio backhaul, its dual-radio design ensures higher bandwidth, lower latency, and stronger interference resistance for seamless, high-performance connectivity.

With NebulaFlex, you get the freedom to manage your network your way—locally via Standalone local GUI or effortlessly through Nebula Cloud, with no IPs or passwords to remember.

Datasheet [NWA90BE](#)

BE5100 (2.4GHz: 2x2:2, 5GHz: 2x2:2) dual-radio access point offers blazingly fast WiFi 7 speeds of up to 5.1Gbps



Smart Mesh MLO with dual-radio backhaul enables dynamic, cable-free deployment while delivering higher performance



Captive portal and IEEE 802.1X authentication support provides enterprise-level security



The 2.5GbE port boosts speed beyond gigabit for a cost-effective, WiFi 7-ready upgrade.



NebulaFlex allows users to switch between standalone or intuitive Nebula cloud managed modes as needed



Benefits

Bringing next generation WiFi within reach

WiFi 7, also known as IEEE 802.11be, represents the next evolution in WiFi standards, supporting all three frequency bands – 2.4GHz, 5GHz, and 6GHz. With its revolutionary technological advancements, it promises to redefine the concept of speed, delivering unprecedented rates to elevate online experiences in the digital realm.

Powered by a Qualcomm quad-core CPU, the NWA90BE access point provides ultra-fast WiFi 7 speeds, ensuring enterprise-grade performance in a compact, small business AP.

MLO: Transforming WiFi 7 for Unprecedented Connectivity

Fundamentally, one of the most pioneering advancements of WiFi 7 is the introduction of MLO (Multiple Link Operation). MLO represents a WiFi technology that empowers devices linked to a WiFi access point (AP) to concurrently transmit and/or receive data through various frequency bands and channels. This entails simultaneous connections across the 2.4GHz, 5GHz, and 6GHz bands, a capability absent in earlier WiFi generations where devices were restricted to a solitary WiFi band connection.

The result is a significant amplification in data throughput, a reduction in latency, and an enhancement in reliability. These outcomes undeniably enhance the user experience and unveil novel opportunities for emerging applications such as VR/AR, online gaming, remote office setups, and cloud computing.

RF First by Design

The advanced RF filter design eliminates interference between the 5GHz and 6GHz bands, while the built-in 4G/5G interference filter allows seamless coexistence with 4G/5G cellular networks and minimizes interference, all of which guarantees a seamless WiFi experience without interruptions.

NebulaFlex – simply manage it your way!

NebulaFlex offers extended flexibility, enabling users to effortlessly switch between standalone mode and our intuitive cloud-managed NCC (Nebula Control Center) modes at any time, without incurring additional costs. This ensures adaptability to changing needs while safeguarding investments in wireless technology.

Specifications

Model	NWA90BE	
Product name	BE5100 4-Stream WiFi 7 Dual-Radio NebulaFlex Access Point	
		
Wireless		
Standard	IEEE802.11 be/ax/ac/n/g/b/a	
MIMO	MU-MIMO	
Wireless speed	2.4GHz	688Mbps
	5GHz	4324Mbps
Frequency band	2.4GHz	<ul style="list-style-type: none">USA (FCC): 2.412 to 2.462 GHzEurope (ETSI): 2.412 to 2.472 GHz
	5GHz	<ul style="list-style-type: none">USA (FCC): 5.15 to 5.35 GHz; 5.470 to 5.850 GHzEuropean (ETSI): 5.15 to 5.35 GHz; 5.470 to 5.725 GHz
Bandwidth	20-, 40-, 80-, 160- and 240-MHz	
Conducted typical transmit output power* ¹	US (2.4GHz/5GHz)	26/25dBm
	EU (2.4GHz/5GHz)	20/25dBm

Model			NWA90BE
RF Design			
Antenna type			Internal Antenna
Antenna gain	2.4GHz		2 dBi, 2x2:2SS
	5GHz		3 dBi, 2x2:2SS
Minimum receive sensitivity			Min. Rx sensitivity up to -99 dBm
WLAN Features			
Band Steering			Yes
WDS/ Mesh*2			Yes
Fast roaming			Pre-authentication, PMK caching and 802.11r/k/v
DCS			Yes
Load balancing			No
Advanced Cellular Coexistence			Yes
Security			
Encryption			WEP/ WPA/WPA2/WPA3
Authentication			IEEE 802.1X/ RADIUS authentication
Access management			L2-isolation/MAC filtering/Rogue AP detection
Networking			
IPv6			Yes
VLANs			Yes
WMM			Yes
U-APSD			Yes
Management			
Operating mode			Cloud managed / standalone
ZON Utility			<ul style="list-style-type: none"> Discovery of Zyxel switches, APs and gateways Centralized and batch configurations <ul style="list-style-type: none"> IP configuration IP renew Device reboot Device locating Web GUI access Firmware upgrade Password configuration
Web UI/CLI			Yes
SNMP			No
Physical Specifications			
Item	Dimensions (WxDxH)(mm/in.)		150 x 150 x 35 / 5.91 x 5.91 x 1.38
	Weight (g/lb.)		412 / 0.91
Packing	Dimensions (WxDxH)(mm/in.)		244 x 168 x 60 / 9.61 x 6.61 x 2.36
	Weight (g/lb.)		785 / 1.73
Included accessories			<ul style="list-style-type: none"> Power adapter Mount plate Mounting screws
MTBF (hr)			870,551
Physical Interfaces			
Ethernet port			1 x 1/2.5GbE LAN
Power			<ul style="list-style-type: none"> Power Adapter: AC100 - 240V - 50/60Hz 0.3A; Output: DC +12V 1.5A PoE (802.3at): power draw 16W
PoE modes	IEEE 802.3af		Not supported
	IEEE 802.3at		Unrestricted
	IEEE 802.3bt		Unrestricted
Environmental Specifications			
Operating	Temperature		0°C to 50°C/32°F to 122°F
	Humidity		10% to 95% (non-condensing)

Model	NWA90BE
Environmental Specifications	
Storage	Temperature -40°C to 70°C/-40°F to 158°F Humidity 10% to 90% (non-condensing)
Certifications	
Radio	FCC Part 15C, FCC Part 15E, FCC Part 2.1091, ETSI EN 300 328, EN 301 893, Draft EN 303 687, EN 50385, EN 50665, EN IEC 62311, LP0002
EMC	FCC Part 15B, EN 301 489-1, EN 301 489-17, EN55032, EN55035, EN61000-3-2/-3, EN60601-1-2, BSMI CNS15936
Safety	EN 62368-1, IEC 62368-1, BSMI CNS15598-1

*1: Maximum transmit power is limited by local regulatory settings.

*2: WDS, ZyMesh, Smart Mesh and Industry's Open Mesh, Easy Mesh are different mesh systems that do not work with one another.

Recommended Accessories

Mounting Accessory

Model	ACCESSORY-ZZ0105F
Product photo	
Description	BAR ceiling clips for ceiling mount Zyxel AP (5 sets)

For more product information, visit us on the web at www.zyxel.com

Copyright © 2025 Zyxel and/or its affiliates. All rights reserved.
All specifications are subject to change without notice.



11/09/25

Datasheet NWA90BE