

## SPECIFICATIONS

|                                  |                                                                                                                   |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------|
| PANEL SIZE                       | 26.5"                                                                                                             |
| PANEL RESOLUTION                 | 3840 x 2160 (UHD)                                                                                                 |
| REFRESH RATE                     | 120Hz                                                                                                             |
| RESPONSE TIME                    | 0.03ms (GtG)                                                                                                      |
| PANEL TYPE                       | QD-OLED                                                                                                           |
| BRIGHTNESS (NITS)                | SDR: 250<br>HDR: 1000                                                                                             |
| VIEWING ANGLE                    | 178°(H) / 178°(V)                                                                                                 |
| ASPECT RATIO                     | 16:9                                                                                                              |
| CURVATURE                        | Flat                                                                                                              |
| CONTRAST RATIO                   | 1500000 : 1                                                                                                       |
| Signal Frequency                 | 30~270 KHz(H) / 40~120 Hz(V)                                                                                      |
| ADOBE RGB / DCI-P3 / SRGB        | 97.5% / 99% / 138.2% (CIE1976)                                                                                    |
| ACTIVE DISPLAY AREA (MM)         | 589.97(H) x 332.93(V)                                                                                             |
| PIXEL PITCH (H X V)              | 0.153(H) x 0.153(V)                                                                                               |
| SURFACE TREATMENT                | Anti-Glare Low Reflection                                                                                         |
| DISPLAY COLORS                   | 1.07B                                                                                                             |
| COLOR BIT                        | 10 bits                                                                                                           |
| HDR SUPPORT                      | VESA DisplayHDR True Black 400                                                                                    |
| VIDEO PORTS                      | 2x HDMI™ 2.1 (UHD@120Hz)<br>1x DisplayPort 1.4a<br>1x Type-C (DP alt.) w/ 98W PD<br>1x Type-C (DP alt.) w/ 15W PD |
| USB Ports                        | 4x USB 5Gbps Type-A<br>1x USB 5Gbps Type-B                                                                        |
| Audio Interface                  | 1x Headphone-out                                                                                                  |
| KENSINGTON LOCK                  | Yes                                                                                                               |
| SPEAKER                          | 2x 2.5W                                                                                                           |
| VESA MOUNTING                    | 100 x 100 mm                                                                                                      |
| POWER TYPE                       | Internal Power Board                                                                                              |
| POWER INPUT                      | 100~240V, 50/60Hz                                                                                                 |
| DYNAMIC REFRESH RATE TECHNOLOGY  | NVIDIA G-SYNC Compatible<br>AMD FreeSync™ Premium Pro                                                             |
| ADJUSTMENT (TILT)                | -5° ~ 20°                                                                                                         |
| ADJUSTMENT (SWIVEL)              | -30° ~ 30°                                                                                                        |
| ADJUSTMENT (PIVOT)               | -90° ~ 90°                                                                                                        |
| ADJUSTMENT (HEIGHT)              | 0 ~ 150 mm                                                                                                        |
| Dimension with Stand (W x D x H) | 611.1 x 200.6 x 560.3 mm<br>(24.06 x 7.90 x 22.06 inch)                                                           |

## FEATURES



### QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



### 4K 120Hz

4K clarity at 120Hz. Everything you see is sharper, and every movement is remarkably fluid.



### MSI M-Mate App

MSI M-Mate brings intuitive monitor control to your fingertips, bridging the gap between your monitor and Mac.



### Tandem OLED

The QD-OLED Penta Tandem™ panel integrates a 5-layer light-emitting structure to boost light efficiency by up to 30%.



### VisiClarity

VisiClarity masterfully integrates Anti-Glare Low Reflection technology to eliminate distracting light, providing a window of pure, undisturbed depth.



### DarkArmor Film

Delivers 40% deeper blacks and a 2.5x more scratch-resistant screen surface.



### AI Care Sensor

AI Care integrates AI sensors to dynamically optimize OLED protection based on real-time usage, making the system even smarter.




### USB Type-C Power Delivery 98W

Built-in an USB Type-C connection with 98W power delivery allows you to effortlessly connect to and charge your devices.

|                                     |                                                                                                                                                                                                                                                                                           |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dimension without Stand (W x D x H) | 611.1 x 73.0 x 367.9 mm<br>(24.06 x 2.87 x 14.48 inch)                                                                                                                                                                                                                                    |
| CARTON DIMENSION (W X D X H)        | 810 x 142 x 478 mm<br>(31.89 x 5.59 x 18.82 inch)                                                                                                                                                                                                                                         |
| WEIGHT (NW / GW)                    | 7 kg (15.43 lbs) / 10.5 kg (23.15 lbs)                                                                                                                                                                                                                                                    |
| ACCESSORIES                         | 1x HDMI™ Cable (2.1), 1x DisplayPort Cable (1.4a), 1x Type-C Cable (3.2 Gen 2), 1x USB Type-B to A Cable (3.2 Gen 1), 1x Power Cord (C13), 1x Quick Guide, 4x VESA Wall Mount Screw, 1x VESA Plate, 4x VESA Plate Screw, 1x VESA Adapter Kit, 1x Cable Clip, 1x Fiber Cloth, Color Report |
| Note                                | HDMI™ : 3840 x 2160 (Up to 120Hz)<br>DisplayPort: 3840 x 2160 (Up to 120Hz)<br>Type-C: 3840 x 2160 (Up to 120Hz)<br>Delta-E (ΔE) ≤ 2<br>Support: HDMI CEC/ MSI Power Link, OLED Care 3.0, KVM 1.0, FW Update, PIP/PBP                                                                     |

CONNECTIONS



- 1. Headphone-out
- 2. 2x HDMI™ 2.1 (UHD@120Hz)
- 3. DisplayPort 1.4a
- 4. Type-C (DP alt.) w/ 15W PD
- 5. Type-C (DP alt.) w/ 98W PD
- 6. USB 5Gbps Type-B
- 7. 2x USB 5Gbps Type-A
- 8. Kensington Lock
- 9. 2x USB 5Gbps Type-A
- 10. AC-in