

Seasonic®

VERTEX PX

1200 W / 1000 W / 850 W / 750 W

1200 W / 1000 W / 850 W

SPECIAL FEATURES

- ❖ Super-High Efficiency, 80 PLUS® Platinum Certified
- ❖ Fully Modular
- ❖ ATX 3.0 and 16-Pin PCIe Gen 5 Cable (12VHPWR)
- ❖ Top-Quality 135 mm Fluid Dynamic Bearing Fan
- ❖ Premium Hybrid Fan Control
- ❖ Tight Voltage Regulation (12 V, 5 V and 3.3 V) [$\pm 3\%$]
- ❖ Gold Plated High Current Terminal (MB, CPU and PCIe)
- ❖ 10 Years Warranty


POWER DISTRIBUTION

Model	+3.3 V	+5 V	+12 V	-12 V	+5 Vsb	Total Power
VERTEX PX-1200	25 A	25 A	100 A	0.3 A	3 A	1200 W
	125 W		1200 W	3.6 W	15 W	
VERTEX PX-1000	25 A	25 A	83 A	0.3 A	3 A	1000 W
	125 W		996 W	3.6 W	15 W	
VERTEX PX-850	25 A	25 A	70 A	0.3 A	3 A	850 W
	100 W		840 W	3.6 W	15 W	
VERTEX PX-750	20 A	20 A	62 A	0.3 A	3 A	750 W
	100 W		744 W	3.6 W	15 W	

750 W



CONNECTOR QUANTITY

Cable							
Model	Main Power (24P / 20P) 610 mm	EPS 12 V / ATX 12 V (8P / 4P) 700 mm	12V HPWR (12+4 Pins) 750 mm	PCI-E (8P / 6P) 750 mm	SATA 950 mm	SATA 3.3 550 mm	Peripheral (4P) 690 mm
VERTEX PX-1200	1	2	1	3	16	2	3
VERTEX PX-1000	1	2	1	3	16	2	3
VERTEX PX-850	1	2	1	3	16	2	3
VERTEX PX-750	1	2	1	2	12	2	3

10 YEARS
WARRANTY

Compliance:   CB     EAC    

Protection Features: OPP / OVP / UVP / SCP / OCP / OTP

Dimensions: 170 mm (L) x 150 mm (W) x 86 mm (H)

Specifications may change without prior notice



Headquarters sales@seasonic.com
USA ssa.sales@seasonic.com
Europe sse.sales@seasonic.com

www.seasonic.com