
Memory Module Specifications



KF564C32BWAK2-64

64GB (32GB 4G x 64-Bit x 2 pcs.)
DDR5-6400 CL32 288-Pin DIMM Kit



DEFAULT SPECIFICATIONS

40 cycles
48ns(min.)
295ns(min.)
32ns(min.)
32ns(min.) 94 V - 0
, ,

DESCRIPTION

Kingston FURY KF564C32BWAK2-64 is a kit of two 4G x 64-bit (32GB) DDR5-6400 CL32 SDRAM (Synchronous DRAM) 2Rx8, memory module, based on sixteen 2G x 8-bit FBGA components per module. Each module kit supports Intel® Extreme Memory Profiles (Intel® XMP) 3.0. Total kit capacity is 64GB. Each module has been tested to run at DDR5-6400 at a low latency timing of 32-39-39 at 1.4V. The SPDs are programmed to JEDEC standard latency DDR5-4800 timing of 40-39-39 at 1.1V. Each 288-pin DIMM uses gold contact fingers. The JEDEC standard electrical and mechanical specifications are as follows:

DEFAULT FEATURES

- Power Supply: VDD = 1.1V Typical
- VDDQ = 1.1V Typical
- VPP = 1.8V Typical
- VDDSPD = 1.8V to 2.0V
- On-Die ECC
- Height 1.66" (42.23mm), w/heatsink


FACTORY TIMING PARAMETERS

Default (JEDEC): DDR5-4800 CL40-39-39 @1.1V
 XMP Profile #1: DDR5-6400 CL32-39-39 @1.4V
 XMP Profile #2: DDR5-6000 CL30-36-36 @1.4V
 XMP Profile #3: DDR5-4800 CL38-38-38 @1.1V


Continued >>





MODULE WITH HEAT SPREADER



MODULE DIMENSIONS







The product images shown are for illustration purposes only and may not be an exact representation of the product. Kingston reserves the right to change any information at anytime without notice.

FOR MORE INFORMATION, GO TO KINGSTON.COM

All Kingston products are tested to meet our published specifications. Some motherboards or system configurations may not operate at the published Kingston FURY memory speeds and timing settings. Kingston does not recommend that any user attempt to run their computers faster than the published speed. Overclocking or modifying your system timing may result in damage to computer components.